

City of Rancho Palos Verdes Department of Public Works

30940 Hawthorne Boulevard Rancho Palos Verdes, CA 90275 P: (310)544-5252 F: (310) 544-5292 Permit No: ENC2018-00058 Issued Date: 03/28/2018 Expiration Date: 05/11/2018

800-227-2600 310-257-1400 800-655-4555 310-540-2977 310-687-2020
thorne Blvd for Soil
N

(A HARD COPY OF PERMIT MUST BE KEPT ON THE JOB SITE AT ALL TIMES)

Access from Hawthorne onto Elkmont Canyon (Perera - Private property) to conduct soil testing bore pits

IMPORTANT NOTICE

Call **(310) 544-5338** to schedule an inspection 72 hours prior to commencing with any work described on this Permit.

Permit valid for a period of 90 calendar days after the approval date shown below. Mock up display and dumpster permits are valid for a period of 30 days after the approval date shown below. Mock up construction permits are valid for 10 days after the approval date shown below.

Printed by: BECKY MARTIN

Schedule and Inspection Online by visiting http://www.rpvca.gov/inspection

Obtain an online account from the Technician at the Public Works Counter.

Schedule an Inspection by Telephone by calling 310-544-5338

Have your permit number, address and contact information available.

Encroachment Permits may require a minimum of 10 working days of FIRST submittal for Excavation, Haul Routes and/or Traffic Control Plans.

All Mock ups shall be installed at least two weeks prior to any Public Hearing related to the proposed construction.

Call "DIG ALERT" at 1-800-227-2600 at least 72 hours prior to any construction.

City Hall Hours - Monday - Thursday 7:30 - 5:30, Friday 7:30 - 4:30 Public Works Telephone - 310-544-5252

WORK SPECIFICATIONS

- All work, unless otherwise specified, shall be done in accordance with the current edition of the STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION.
- Any staging of materials in the City Right-of-Way requires prior approval.
- Haul Routes must be approved 48 Hours prior to entering the City.
- The Permittee/Contractor must follow the latest National Pollutant Discharge Elimination System (NPDES) & Best Management Practices (BMP's) guidelines.
- Before work on any sewer line begins, a permit must be issued by the City of Rancho Palos Verdes Building and Safety Division in addition to this permit. For information on sewer permits call (310) 544-5244 and ask for Building and Safety.
- When permittee tunnels under existing curbs, gutters and sidewalks, the excavated trench shall be back-filled with cement grout as described in the Standard Specifications.
- A.C. Pavement shall be saw-cut beyond edge of trench as specified by APWA Standards.
- · Asphalt shall be placed in one-inch lifts or as directed by Department of Public Works Staff.
- When compaction or material tests are required, all costs are to be borne by the permittee.
- A one-sack sand slurry mixture may be required for compaction where excavation interferes with traffic flow or where work is within the roadway portion of an intersection.
- All excavations must be back-filled or plated at the end of the workday. The City reserves the right to require the permittee to plate open trenches in lieu of back filling.
- Permanent pavement repairs shall be made within 25 calendar days after excavation work is completed. Inspector's approval is required before permanent repairs are made.
- Tree trunks shall be cut to within 4" of curb height. All tree trunks and roots shall be ground to a depth of 18" below grade by a mechanical stump grinder to the satisfaction of the Department of Public Works staff. All wood chips shall be removed, hole filled and compacted with topsoil.

TRAFFIC CONTROL STANDARD REQUIREMENTS

- Traffic controls throughout permit construction shall conform to the latest edition of the State of California MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) FOR USE IN PERFORMANCE OF WORK UPON HIGHWAYS. Permittee shall provide and maintain all such signs, lights, and devices. All barricades in use after sunset must have portable flashers.
- Traffic may be restricted only between the hours of 9:00 a.m. and 3:00 p.m. on all major and secondary highways and subject to review of the Traffic Engineer.
- One lane of traffic in each direction shall be maintained at all times on all major and secondary highways.
- Pedestrian walkways must be maintained with safety fencing or barrier separation for adjacent excavation.
- The cost of any damage to traffic signal control devices shall be the permittee's responsibility and it shall be brought to the immediate attention of the inspector. The Permittee/Contractor shall be responsible for the replacement cost of any inductive loops in the ground (wire sensors for traffic signals) that are in conflict with or damaged by construction.

DUMPSTER REQUIREMENTS - MUST OBTAIN CONTAINER FROM A CURRENTLY APPROVED VENDOR

- · Keep the street clean from debris at all times.
- Do not block/obstruct traffic motorists' line of sight in any direction.
- · Dumpster shall not infringe on any driveway approach, Fire Hydrant, Emergency facility, or utility cabinet.
- Dumpsters must have cones or delineators, reflectors, and reflectorized tape at corners.

CURB AND GUTTER, DRIVEWAY APPROAC, SIDEWALK AND CURB CORE REQUIREMENTS

City's trench standards shall be adhered to.

- Remove any/all markings following construction.
- Remove and Replace curb and gutter at the edge of the asphalt and haul materials to a recycling center. Provide Load Ticket to the Inspector. (Do not cut Asphalt in the street unless directed to do so by the Department of Public Works staff).
- Install monolithic section of curb and gutter.
- Must remove and replace Concrete Score line to Score line or as directed by the City staff.
- Install a minimum of 6-inch thick 3,250-PSI concrete on drivable surfaces and a minimum of 4-inch thick 3,250-PSI concrete in other places.
- Follow American Public Works Association (APWA) standards for Curb Core (Standards available at the City of Rancho Palos Verdes/Department of Public Works).

www.rpvca.gov